

DA 2360

Extractor unit



- Customised kitchen design – fully integrated in 584mm width
- Space-saving – suitable for narrow wall units over 30 cm deep
- Powerful – 600m<sup>3</sup>/h on the booster setting
- Efficient filtration – 10-layer stainless-steel grease filter
- Safe and easy to clean – Miele CleanCover

|   |             |
|---|-------------|
| <b>Construction type</b>  |             |
| Integrated extractor  | •           |
| <b>Design</b>   |             |
| Colour  | No colour   |
| RAL colours available as customisation on request   | •           |
| Customisation possible on request   | •           |
| <b>Operating modes</b>  |             |
| Type of air guide   | Convertible |
| <b>User convenience</b>   |             |
| Electronic controls   | •           |
| Light-touch controls  | •           |
| Power levels (number without Booster level)   | 3           |
| Booster level   | •           |
| <b>Cleaning convenience</b>   |             |
| CleanCover  | •           |
| <b>Filter system</b>  |             |
| Number of dishwasher safe stainless-steel grease filters (10-ply)                           | 1           |
| <b>Lighting</b>   |             |
| LED   | •           |
| Light intensity in Lx   | 350         |
| Colour temperature in K   | 3,000       |
| <b>Fan</b>  |             |
| Dual-action fan   | •           |
| AC motor  | •           |
| <b>Air throughput with max. duct diameter in extraction mode (not for external version)</b> |             |
| Air throughput in Level 1 (m <sup>3</sup> /h)   | 250         |
| Air throughput in Level 2 (m <sup>3</sup> /h)   | 300         |
| Air throughput in Level 3 (m <sup>3</sup> /h)   | 360         |
| Air throughput in Booster level (m <sup>3</sup> /h)   | 600         |
| Sound power in Level 1 (dB(A) re 1 pW)  | 47          |
| Sound power in Level 2 (dB(A) re 1 pW)  | 48          |
| Sound power in Level 3 (dB(A) re 1 pW)  | 52          |
| Sound power in Booster level (dB(A) re 1 pW)  | 64          |
| Sound pressure in Level 1 (dB(A) re 20 µPa)   | 31          |
| Sound pressure in Level 2 (dB(A) re 20 µPa)   | 34          |
| Sound pressure in Level 3 (dB(A) re 20 µPa)   | 38          |
| Sound pressure in Booster level (dB(A) re 20 µPa)   | 50          |

DA 2360

Extractor unit



| <b>Air throughput in recirculation mode</b>                |      |
|--|------|
| Air throughput in Level 1 (m <sup>3</sup> /h)              | 190  |
| Air throughput in Level 2 (m <sup>3</sup> /h)              | 250  |
| Air throughput in Level 3 (m <sup>3</sup> /h)              | 320  |
| Air throughput in Booster level (m <sup>3</sup> /h)        | 500  |
| Sound power in Level 1 (dB(A) re 1 pW)                     | 54   |
| Sound power in Level 2 (dB(A) re 1 pW)                     | 60   |
| Sound power in Level 3 (dB(A) re 1 pW)                     | 64   |
| Sound power in Booster level (dB(A) re 1 pW)               | 72   |
| Sound pressure in Level 1 (dB(A) re 20 µPa)                | 39   |
| Sound pressure in Level 2 (dB(A) re 20 µPa)                | 45   |
| Sound pressure in Level 3 (dB(A) re 20 µPa)                | 49   |
| Sound power in Booster level (dB(A) re 1 pW)               | 57   |
| <b>Safety</b>  |      |
| Safety switch-off  | •    |
| <b>Technical data</b>                                      |      |
| Canopy width in mm   | 584  |
| Canopy height in mm  | 63   |
| Canopy depth in mm   | 297  |
| Net weight in kg   | 11.0 |
| Length of supply lead in m                                 | 1.5  |
| Standard plug fitted                                       | •    |
| Total rated load in kW                                     | 0.23 |
| Voltage in V   | 230  |
| Fuse rating in A   | 10   |
| Number of phases   | 1    |
| <b>Installation notes</b>                                  |      |
| Extraction ducting connection at top                       | •    |
| Extraction connection at top and rear                      | •    |
| Diameter of extraction ducting connection in mm            | 150  |
| <b>Standard accessories</b>                                |      |
| Non-return flap  | •    |
| Adapter to reduce ducting diameter from 150 mm to 125 mm Ø | •    |